



emergency overflow



Capacity	
Organic daily load	0,3 kg BOD ₅
Hydraulic daily load	0,75 m ³
Water Levels	
H _{BB,min}	850 mm
H _{BB,max}	1010 mm
HW _{ges}	1100 mm
H _P	350 mm
H _S	750 mm
Dimension	
Length L	2080 mm
Width B	1565 mm
Height H	2010 mm
Inflow E	205/430 mm
Outflow A	435 mm



Maxi (as option)



<p>D</p> <p>Klaro E Professional 5 EW TD-Mini Carat 2700 L / 713,3 gal.</p>			<p>Artikel-Nr. product no. article no. artículo no.</p>
<p>GB Klaro E Professional 5 inh. TD-Mini Carat 2700 L / 713,3 gal.</p>	<p>ES Klaro E Professional 5 PE Cúpula Mini Carat 2700 L / 713,3 gal.</p>	<p>FR Klaro E Professional 5 EH mini-dôme Carat 2700 L / 713,3 gal.</p>	<p>revision</p>
<p>gezeichnet drawn ISC</p>	<p>Gewicht weight 120 kg</p>	<p>Otto Graf GmbH Carl-Zeiss-Str. 2-6 DE-79331 Teningen mail@graf.info www.graf.info</p>	
<p>Datum date 2016.08.15</p>	<p>Toleranz tolerance +/- 3%</p>		
<p>Maßstab scale unmaßst.</p>	<p>Einheiten units mm [inch] gal. = US gal.</p>		